## Innovative Vacuum Technology Innovative Vacuum Technology







Porschestraße 12 63512 Hainburg | Germany

Phone: +49618293510 sales@hs-group-gmbh.de www.hs-group-gmbh.de





## **INLINE SPUTTER COATER**

## **DELTALINE-SERIES**



Description	Unit	Data
Substrate size max*	[mm]	400 x 400/600 x 600/800 x 800
Substrate height max*	[mm]	15
Carrier orientation	-	horizontal or vertical
Speed range	-	0.2 10 m/min
High vacuum pumps	-	turbo-molecular pumps, cryo pumps
Temp. pre-treatment	[°C]	20 350 °C
Plasma pre-treatment	-	glowing/etching
Ultimate vacuum	[mbar]	< 5 x 10-7 mbar
Magnetrons	-	planar/rotatable
Sputter modes	-	DC/pulsed DC/MF/RF
Layers	-	Metals/alloys/multilayer/oxides
Chamber configuration	-	Modular arrangement
Chamber material	-	SS 1.4301
*Other specifications on request		

SUITABLE FOR R&D AND PRODUCTION

EXTENSIVE RECIPE MANAGEMENT

DATA MANAGEMENT FOR DOCUMENTATION

HIGHLY EFFECTIVE VACUUM SYSTEM

LOADING / UNLOADING WITH DUST COVER

FULLY AUTOMATIC PROCESS CONTROL

AUTOMATIC SUBSTRATE CHANGER 10 / 15-FOLD

APPLICATIONS:

MICROELECTRONICS, DISPLAY, SOLAR, GLASS, OTHER PLANE SUBSTRATES



